

IMPACT WRENCH 3/4" MI-20S

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-20S is developed for assembly- and disassembly purposes. The Twin-Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. Due to its compact build, the tool is very suitable for jobs in small spaces.

Characteristics:

- Ergonomic design, well balanced
- Compact and durable
- Clutch: Twin-Hammer
- Adjustable power, 4 positions
- Exhaust through isolated grip, with silencer

Related products



DO605421001

Impact Socket Set 3/4" deep 10-parts



AC40A-F04-D

Frl Unit



DO605401001

Impact Socket Set 3/4" 10-parts

Related accessories



DOESR-2

Ret Ring



DOESR-1 Ret Ring



Specifications

 Brand
 Toku

 Square Drive
 3/4"

 Version
 R+H

 Bolt capacity (mm)
 20

Impact mechanism Twin-Hammer

RPM 4500 Torque (Nm) 900

Force adjustment R/L 4 Standen

 Airconsumption (I/s)
 15

 Weight (kg)
 3,25

 Airconnection
 PT 3/8"

 Airpress max. (MPa)
 0,63

 mm A
 164

 mm B
 40

 Hosediameter (mm)
 10

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 2150

Vibration standard EN ISO 28927-2

 Vibration value (m/s²)
 8,3

 Vibration uncertainty (m/s²)
 1,32

 Sound standard
 ISO 15744

 Sound pressure (dB(A))
 90

 Sound power (dB(A))
 101

 Sound uncertainty (dB(A))
 3

EAN 8717981396832

