

# IMPACT WRENCH 3/4" MI-20S

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-20S is developed for assembly- and disassembly purposes. The Twin-Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. Due to its compact build, the tool is very suitable for jobs in small spaces.

#### Characteristics:

- Ergonomic design, well balanced
- Compact and durable
- Clutch: Twin-Hammer
- Adjustable power, 4 positions
- Exhaust through isolated grip, with silencer

#### Related products



DO605421001

Impact Socket Set 3/4" deep 10p



AC40A-F04-D

Modular FRL unit



DO605401001

Socketset 3/4" 10-Parts

#### Related accessories



DOESR-2

Ret Ring



DOESR-1

Ret Ring



#### Specifications

Brand	Toku
Square Drive	3/4"
Version	R+H
Bolt capacity (mm)	20
Impact mechanism	Twin-Hammer
RPM	4500
Torque (Nm)	900
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	15
Weight (kg)	3,25
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	164
mm B	40
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	2150
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	8,3
Vibration uncertainty (m/s <sup>2</sup> )	1,32
Sound standard	ISO 15744
Sound pressure (dB(A))	90
Sound power (dB(A))	101
Sound uncertainty (dB(A))	3
EAN	8717981396832

