

150MM TWO-HAND SANDER RRI-T6250-5CV

This RED ROOSTER palm sander is vibration-reduced. The body has a rubber cover for maximum grip. The simplicity of the construction results in a reliable tool.
Applications in: Car-bodywork, metal- and woodworking industry.

Characteristics:

- * Ergonomic design, well balanced.
- * Exhaust air is silenced.
- * Hook & Loop pad.
- * Lightweight.
- * Adjustable speed.
- * Excenterstroke 5 mm.
- * Version for connection to central dust extraction (for 32mm hose size).



Specifications

| | |
|--|-----------------------------|
| Brand | RedRoosterIndustrial |
| RPM | 12000 |
| Airconsumption (l/s) | 4,9 |
| Weight (kg) | 1,0 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 262 |
| mm B | 104 |
| Hosediameter (mm) | 6,5 |
| Spindle | 5/16" UNF |
| Sanding pads | 150 |
| Power (kW) | 0,3 |
| Excenter stroke (mm) | 5 |
| Vibration standard | EN ISO 28927-3 |
| Vibration value (m/s²) | 3,24 |
| Vibration uncertainty (m/s²) | 1,11 |
| Sound standard | 1,11 |
| Sound pressure (dB(A)) | 73 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981204281 |

