

150MM TWO-HAND SANDER RRI-T6250-5CV

This RED ROOSTER palm sander is vibration-reduced. The body has a rubber cover for maximum grip. The simplicity of the construction results in a reliable tool.
Applications in: Car-bodywork, metal- and woodworking industry.

Characteristics:

- * Ergonomic design, well balanced.
- * Exhaust air is silenced.
- * Hook & Loop pad.
- * Lightweight.
- * Adjustable speed.
- * Excenterstroke 5 mm.
- * Version for connection to central dust extraction (for 32mm hose size).



Specifications

Brand	RedRoosterIndustrial
RPM	12000
Airconsumption (l/s)	4,9
Weight (kg)	1,0
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	262
mm B	104
Hosediameter (mm)	6,5
Spindle	5/16" UNF
Sanding pads	150
Power (kW)	0,3
Safety standard	EN ISO 11148-8
Excenter stroke (mm)	5
Vibration standard	EN ISO 28927-3
Vibration value (m/s²)	3,24
Vibration uncertainty (m/s²)	1,11
Sound standard	1,11
Sound pressure (dB(A))	73
Sound uncertainty (dB(A))	3
EAN	8717981204281

