RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

# 18V-3/8" SQ, TRANSDUCER NUTRUNNER RRI-BCA60S3

**RED ROOSTER Cordless transducerized angle wrench. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.**
**Characteristics:**
- **Brushless motor**
- **18 Volt Lithium-Ion battery**
- **LED status indicates OK - NOK - REVERSE - BATTERY LOW**
- **Tightening mode setting – Torque or Angle**
- **Programmable torque**
- **Programmable angle limits**
- **Programmable speed**
- **Group check / counting**
- **8 programs including sequence**
- **Compact and light weight**
- **The flat battery pack offers stability**
- **Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately**

## Related products



**BB200D-325**
**18V 2.5Ah Battery, Li-ion**



**BB200D-350**
**18V 5.0Ah Battery, Li-ion**



**B84192B**
**18-20V Charger**

## Related accessories



**33116-B200D-01**
**Protection Cover**



**61022-TH005**
**Tool Holder**



**32088-NPA-01**
**Cable**



**33116-B200D-02**
**Protection Cover**



**33116-WRCA-02**
**Protection Cover RRI-BCA50&60**



## Specifications

| | |
|---|---|
| **Brand** | **RedRoosterIndustrial** |
| **Square Drive** | **3/8"** |
| **Bolt capacity (mm)** | **10** |
| **RPM** | **50 - 170** |
| **Torque (Nm)** | **25 - 60** |
| **Weight w/o battery (kg)** | **2,16** |
| **mm A** | **535** |
| **mm B** | **42,5** |
| **Battery voltage (Volt)** | **18** |
| **Battery type Li-ion….(Ah)** | **2,5 / 5,0** |
| **Vibration standard** | **EN ISO 28927-2** |
| **Vibration value (m/s²)** | **1,2** |
| **Vibration uncertainty (m/s²)** | **0,4** |
| **Sound standard** | **ISO 15744** |
| **Sound pressure (dB(A))** | **71** |
| **Sound uncertainty (dB(A))** | **3** |
| **EAN** | **8717981418732** |

