

# IMPACT WRENCH 1" MI-38ESR

This industrial impact wrench by Toku has proven capabilities. The MI-38ESR is developed for tightening and untightening applications. The Twin Hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is especially suitable for use in the tire industry.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* Power adjustable, 4 positions

**Related products**



**DO0100-1-007**  
 Impact Socket Set Long 1" 7-parts

**Related accessories**



**ATLUB**  
 Air Tool Oil, 1 litre



**DOESR-3**  
 Ret Ring



**Specifications**

<b>Brand</b>	Toku
<b>Square Drive</b>	1"
<b>Version</b>	R+H
<b>Bolt capacity (mm)</b>	36
<b>Impact mechanism</b>	Twin-Hammer
<b>RPM</b>	3700
<b>Torque (Nm)</b>	1850
<b>Force adjustment</b>	R/L 4 Standen
<b>Airconsumption (l/s)</b>	11,6
<b>Weight (kg)</b>	7,7
<b>Airconnection</b>	PT 1/2"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	337
<b>mm B</b>	50
<b>Hosediameter (mm)</b>	13
<b>Safety standard</b>	EN ISO 11148-6
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	12,2
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,70
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	96
<b>Sound power (dB(A))</b>	107
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981038572

