

# IMPULSE WRENCH 1/4" HEX 18-30NM YX-180SA

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Straight model.

## Related products



**HTB-0**  
Spring Balancer Hosereel

## Related accessories



**ATLUB**  
Air Tool Oil, 1 litre



## Specifications

|  |                |
|--|----------------|
| <b>Brand</b>                                   | Yokota         |
| <b>Bolt capacity (mm)</b>                      | 4 - 6          |
| <b>RPM</b>                                     | 10500          |
| <b>Torque (Nm)</b>                             | 18 - 30        |
| <b>Weight (kg)</b>                             | 0,96           |
| <b>Airconnection</b>                           | PT 1/4"        |
| <b>Airpress max. (MPa)</b>                     | 0,63           |
| <b>Airconsumption fullload (l/s)</b>           | 4,2            |
| <b>mm A</b>                                    | 220            |
| <b>mm B</b>                                    | 23             |
| <b>Hosediameter (mm)</b>                       | 6,5            |
| <b>Square Drive / Hexagon</b>                  | 1/4"           |
| <b>Air consumption no load (l/s)</b>           | 7,8            |
| <b>Vibration standard</b>                      | EN ISO 28927-2 |
| <b>Vibration value (m/s<sup>2</sup>)</b>       | < 2,5          |
| <b>Vibration uncertainty (m/s<sup>2</sup>)</b> | 1              |
| <b>Sound standard</b>                          | ISO 15744      |
| <b>Sound pressure (dB(A))</b>                  | 83             |
| <b>Sound power (dB(A))</b>                     | 94             |
| <b>Sound uncertainty (dB(A))</b>               | 3              |
| <b>EAN</b>                                     | 8717981136162  |

