

MANIPULATOR 250 KG TCR-250ME

The RED ROOSTER Compact Hoist are suitable for "Material-Handling".
The pendant control is direct on the lower hook so the operator can control and position the load easy and direct.
Lifting height 3 meters. The perfect solution for horizontal movements is the combination with a push trolley.

Characteristics:

- * Pendant control direct on the lower hook
- * Optimum load control, very precise positioning
- * One-hand control
- * Variable speed control
- * Soft start and stop, no shock movements
- * Handle can be positioned for left-hand or right-hand operation
- * Endstop system

Related products



4X12RTS
Chain RTS EN 818-7



AC30-F03DM-8-B
Modular FRL Unit



4X12RS60
Chain RS60 Stainless Steel EN818-7



Specifications

Brand	RedRooster
4-button control with emergency stop- (VTR-4E)	
Number of chain falls	1
Lowering speed full load (m/min)	16,5
Lowering speed 0-load (m/min)	12,4
Weight incl. 3m lift (kg)	11
Lifting speed full load (m/min)	8
Lifting speed 0-load (m/min)	16,7
Chain weight (kg/m)	0,35
Chain (mm)	4,0 x 12,0 (HD)
Chainbag/Chainbucket	+
Loadlimiter	-
Trolley	+
Airconnection	3/8" BSPT
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	11,7
mm A	286
mm B	174
mm C	112
mm D	837
mm E	15
mm F	194
mm G	102
mm H	92
mm I	184
mm J	123
mm K	61
mm L	152
mm M	74
mm N	78
mm O	36
Hosediameter (mm)	13
SMC Airtreatment unit	AC30-F03DM-8-B