RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

AIR CHAIN HOIST 1000 KG
TCR-1000C2

These RED ROOSTER Air Chain Hoists are especially developed for heavy industrial use.
Robust cast steel body. Valveblock same for all models, less spare parts. Standard with load limiter.
Characteristics:
*** Precise variable speed control (cord - and pendant control)**
*** Optimum control of the load, very precise positioning**
*** Compact design**
*** Endstop system**
*** Load limiter built-in without loss of headroom**
*** Cord control or pendant control**
*** Quiet, low noise level, silenced**
*** Air pressure 0,4 - 0,63 MPa (4 - 6,3 Bar)**



Related products


AC40-F04DE-D
Frl Unit


6,3X19,1RS60
Chain RSA60 DIN 5684-6


6,3X19,1RTS
Chain RTS EN 818-7

Specifications

Brand	RedRooster
Number of chain falls	2
Lowering speed full load (m/min)	9,0
Lowering speed 0-load (m/min)	6,5
Weight incl. 3m lift (kg)	35,2
Lifting speed full load (m/min)	5,3
Lifting speed 0-load (m/min)	9,5
Chain weight (kg/m)	1,8
Chain (mm)	6,3 x 19,1
Airconnection	1/2" BSPT
Airpress max. (MPa)	0,63
mm A	519
mm B	212
mm C	162
mm D	50
mm E	156
mm F	186
mm G	29
mm H	40
mm I	29
mm J	25
mm X	100
mm Z	250
Hosediameter (mm)	13
Capacity (kg)	1000
Air consumption lifting (l/s)	25
Air consumption lowering (l/s)	27
EAN	8717981100415

