

# IMPULSE WRENCH 3/8" SHUT-OFF RRI-BIM25T

RED ROOSTER Cordless shut-off impulse wrench. High tightening speed combined with good accuracy. No reaction forces during the tightening process. Brushless motor for long motor life and high efficiency. No tightening functionality when battery charge is low, thus process safety improves. Very well suited in areas where cables and hoses impede handling flexibility of tools, such as interiors of cars, coaches and trains.

**Characteristics:**




- Brushless motor
- Lithium-Ion battery (choice for 2,5 Ah or 5,0 Ah capacity)
- LED status indicates: Reverse, OK, NG, Battery low
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Variable speed control with non-contact trigger
- Run-down speed: 4500 RPM

Battery and charger to be ordered separately

**Related products**

-  **BB200D-325**  
20V 2.5Ah Battery, Li-ion
-  **B74SC180B**  
Programmer
- BB200D-350**  
20V 5.0Ah Battery, Li-ion
- B84192B**  
18-20V Charger
- E86B-VD**  
Power Cord (EU)

**Related accessories**

-  **33116-B200D-01**  
Protection Cover
-  **61022-TH005**  
Tool Holder
-  **33116-B200D-02**  
Protection Cover
-  **B10PW15**  
Back Panel Cover (ALU)
- C16PW-25**  
Protection Cover RRI-BIM25/35



**Specifications**

Brand	RedRoosterIndustrial
Square Drive	3/8"
Bolt capacity (mm)	6 - 8
RPM	4500
Torque (Nm)	15 - 25
Weight w/o battery (kg)	1,18
mm A	29
mm B	234
Battery voltage (Volt)	20
Battery type Li-ion....(Ah)	2,5 / 5,0
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	5,38
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	73,9
Sound uncertainty (dB(A))	3
EAN	8717981326259

