

SCREWDRIVER WITH HAMMERMECHANISM MID-600

This Toku screwdriver is developed for assembly in wood-working and furniture-industry. It has a 2-hammer clutch for powerfull operation.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable in 4 positions
- * Exhaust through isolated grip, with silencer
- * Free of reaction forces

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



ATLUB
Air Tool Oil, 1 litre



Specifications

| | |
|---|----------------|
| Brand | Toku |
| Bolt capacity (mm) | 3 - 5 |
| RPM | 9500 |
| Torque (Nm) | 90 |
| Airconsumption (l/s) | 5,0 |
| Weight (kg) | 0,9 |
| Hexagon | 1/4" |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 149 |
| mm B | 22 |
| mm C | 161 |
| Hosediameter (mm) | 6,5 |
| Execution | Pistol |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | 7,6 |
| Vibration uncertainty (m/s ²) | 1,24 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 88 |
| Sound power (dB(A)) | 99 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981148349 |

