

SCREWDRIVER WITH HAMMERMECHANISM MID-600

This Toku screwdriver is developed for assembly in wood-working and furniture-industry. It has a 2-hammer clutch for powerfull operation.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable in 4 positions
- * Exhaust through isolated grip, with silencer
- * Free of reaction forces

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	Toku
Bolt capacity (mm)	3 - 5
RPM	9500
Torque (Nm)	90
Airconsumption (l/s)	5,0
Weight (kg)	0,9
Hexagon	1/4"
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	149
mm B	22
mm C	161
Hosediameter (mm)	6,5
Execution	Pistol
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	7,6
Vibration uncertainty (m/s ²)	1,24
Sound standard	ISO 15744
Sound pressure (dB(A))	88
Sound power (dB(A))	99
Sound uncertainty (dB(A))	3
EAN	8717981148349

