

HIGH TORQUE GEAR WRENCH 1500 NM

RRI-BEC150

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. This gear wrench has an extremely high speed.

Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

Related accessories

-  SW40-283-0102
Hanger
-  31084-360F
36V Charger
-  31022-GW019
Reaction Welding Ring RRI-BEC150/250
-  31022-GW001
Reaction Bar RRI-BEC025-250
-  31022-GW008
Sliding Reaction Plate RRI-BEC150/250
-  DO6055S055
High Torque Socket 1" x 55mm
-  31022-GW010
Reaction Bar RRI-BEC025-250
-  DO6055S030
High Torque Socket 1" x 30mm
-  Koffer RRI-BEC150
-  Case RRI-BEC150
-  31022-GW007
Secondary Handle RRI-BEC/120/150/250
-  31022-GW009
Reaction Bar RRI-BEC025-250
-  BW203
Back Up Wrench 12-Pt A/F 55 mm, max 5694 Nm
-  31022-GW027
double sided reaction arm
-  31022-GW013
Reaction Bar Adapter RRI-BEC150/250
-  33257-RRI-BEC250
Standard Reaction Bar RRI-BEC150/250



Specifications

Brand	RedRoosterIndustrial
Square Drive	1"
Bolt capacity (mm)	20 ~ 36
RPM	45 / 9,6
Torque (Nm)	300 ~ 1500
Weight w/o battery (kg)	6,2
mm A	170
mm B	80
mm C	355
mm D	228
mm E	273
mm F	Ø 82
mm L	70
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	1
Vibration uncertainty (m/s ²)	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	82
Sound uncertainty (dB(A))	3
EAN	8717981444090

