

IMPACT WRENCH 1/2 MI-16M1/2

This TOKU Impact Wrench has an excellent weigth/power ratio. The MI-16 is developed for assembly- and disassembly purposes. The Twin Hammer impactmechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

Related products



D0605201003

Impact Socket Set 1/2" 10-parts




D0605222601

Impact Socket Set 1/2"deep 26-parts



D0691121301





D069523108

Impact Socket Set 1/2" deep 10-parts



D0652260701

Impact Socket Set 1/2" triple square

Related accessories



ATLUB

Air Tool Oil, 1 litre



Specifications

RPM

| Brand | Toku |
|--------------------|------|
| Square Drive | 1/2" |
| Version | R+H |
| Bolt capacity (mm) | 12 |

Impact mechanism Twin-Hammer

6200

Torque (Nm) 330

Force adjustment R/L 4 Standen

Airconsumption (I/s) 9.3

 Airconsumption (I/s)
 9,3

 Weight (kg)
 1,5

 Airconnection
 PT 1/4"

 Airpress max. (MPa)
 0,63

 mm A
 170

 mm B
 27

 Hosediameter (mm)
 6,5

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm)550Vibration standard1,18Vibration value (m/s²)6,9Vibration uncertainty (m/s²)1,08Sound standardISO 15744Sound pressure (dB(A))89Sound power (dB(A))100

Sound uncertainty (dB(A))

EAN 8717981324583

