

IMPACT WRENCH 1/2

MI-16M1/2

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-16 is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

Related products

-  **D0605201003**
Impact Socket Set 1/2" 10-parts
-  **D0605222601**
Impact Socket Set 1/2" deep 26-parts
-  **D0691121301**
Impact Socket Set 1/2" & bits 13-parts
-  **D069523108**
Impact Socket Set 1/2" deep 10-parts
-  **D0652260701**
Impact Socket Set 1/2" triple square
-  **AC30A-F03E-D**
Frl Unit

Related accessories

-  **ATLUB**
Air Tool Oil, 1 litre



Specifications

Brand	Toku
Square Drive	1/2"
Version	R+H
Bolt capacity (mm)	12
Impact mechanism	Twin-Hammer
RPM	6200
Torque (Nm)	330
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	9,3
Weight (kg)	1,5
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	170
mm B	27
Hosediameter (mm)	6,5
Max. breakaway torque (Nm)	550
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	6,9
Vibration uncertainty (m/s ²)	1,08
Sound standard	ISO 15744
Sound pressure (dB(A))	89
Sound power (dB(A))	100
Sound uncertainty (dB(A))	3
EAN	8717981324583

