
















# HAMMER VIBRATION REDUCED RRI-4021/4

The new RED ROOSTER Industrial RRI-4021/4 vibration reduced chipping hammer, features an open grip handle for ease of use & is fitted with solid steel screw retainer that allows use of both pointed and wide cutting chisels whilst fully eliminating the risk of chisel retaining spring breakages. Suitable for close work in confined spaces where greater manoeuvrability is required.

## Characteristics:

- Ergonomic & well balanced design
- Compact and light weight
- Low Vibration for greater operator comfort
- Solid steel screw retainer

## Related products

-  CB51193180  
Slotting Tool W.Carbide Tip L=180
-  CB51112180  
Flat Chisel
-  CB51103185  
45mm Wide Chisel, L=185mm
-  CB51103250  
Flat Chisel
-  CB51109165  
Flat Chisel
-  CB51116180  
Tail Pipe Cutter
-  CB51123180  
Claw Ripper/PannelCutter
-  CB51109180  
Flat Chisel
-  CB51109250  
Flat Chisel
-  CB51102190  
Scraper, bent
-  CB51115250  
Moil Point
-  CB51115180  
Moil point chisel
-  CB51114180  
Double Blade panel cutter
-  CB51117180  
Spotweld Breaker
-  CB51104190  
Wide Cutting chisel bent

## Related accessories

-  TH-1830A34



## Specifications

Brand	RedRoosterIndustrial
Airconsumption (l/s)	10,0
Weight (kg)	2,2
Shank size (mm)	H^11,0 x R^12,7 x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	255
mm B	100
Stroke (mm)	30
Strokes per minute	4500
Energy (J/Stroke)	3,5
Hosediameter (mm)	10
Piston (mm)	18
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-9
Vibration value (m/s <sup>2</sup> )	10,06
Vibration uncertainty (m/s <sup>2</sup> )	2,96
Sound standard	ISO 15744
Sound pressure (dB(A))	88
Sound power (dB(A))	99
Sound uncertainty (dB(A))	3
EAN	8717981293780

