

# 20V SCREWDRIVER 1/4 HEX SHUT-OFF RRI-BS3H2

RED ROOSTER Cordless shut-off screwdriver. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains. Contactless trigger and forward / reverse switch for a long lifetime.

Characteristics:








- Brushless motor
- 20 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 200 to 500 RPM
- Compact and light weight

Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

## Related products

-  BB200D-325  
20V 2.5Ah Battery, Li-ion
-  B74SC180B  
Programmer
- BB200D-350  
20V 5.0Ah Battery, Li-ion
- B84192B  
18-20V Charger
- E86B-VD  
Power Cord (EU)

## Related accessories

-  D39SC180B-1  
Suspension Bail
-  33116-B200D-01  
Protection Cover
-  61022-TH005  
Tool Holder
-  33116-B200D-02  
Protection Cover
-  61022-TH003  
Tool Holder, diameter 58mm
-  33116-SCEP-01  
Protection Cover
-  00-4507  
Torque Adjust Key RRI screwdriver



## Specifications

Brand	RedRoosterIndustrial
Bolt capacity (mm)	4
RPM	200 - 500
Torque (Nm)	0,8 - 3
Weight w/o battery (kg)	1,0
Hexagon	1/4"
mm A	203
mm B	238
Battery voltage (Volt)	20
Battery type Li-ion....(Ah)	2,5 / 5,0
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	0,1
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	57,4
Sound uncertainty (dB(A))	3
EAN	8717981400645

