

# 50MM MINI DISC SANDER RRS-60152

This mini-sander of RED ROOSTER has a ROLOC system for quick and sure exchange of sanding discs. The RPM is adjustable. Very simple and robust construction

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Exhaust air silenced through grip
- \* Wide starter for operator comfort
- \* Body in composite material
- \* Lightweight



## Specifications

<b>Brand</b>	<b>RedRooster</b>
<b>RPM</b>	<b>15000</b>
<b>Airconsumption (l/s)</b>	<b>4,9</b>
<b>Weight (kg)</b>	<b>0,54</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>100</b>
<b>mm B</b>	<b>140</b>
<b>Hosediameter (mm)</b>	<b>10</b>
<b>Spindle</b>	<b>1/4" - 20</b>
<b>Power (kW)</b>	<b>0,3</b>
<b>Safety standard</b>	<b>EN ISO 11148-8</b>
<b>Excenter stroke (mm)</b>	<b>-</b>
<b>Vibration standard</b>	<b>EN ISO 28927-1</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>3,11</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>0,8</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>80</b>
<b>Sound power (dB(A))</b>	<b>91</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981298716</b>

