

18V SCREWDRIVER 1/4 HEX SHUT-OFF RRI-BS9H2

RED ROOSTER Cordless shut-off screwdriver. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains. Contactless trigger and forward / reverse switch for a long lifetime. Characteristics:

- Brushless motor
- 18 Volt Lithium-Ion battery
- LED status indicates OK NOK REVERSE BATTERY LOW
- Adjustable torque
- Speed 300 to 800 RPM
- Compact and light weight

Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

Related products



BB200D-325





B74SC180B





BB200D-350 18V 5.0Ah Battery, Li-ion



B84192B





E86B-VD Power Cord (EU)

Related accessories



D39SC180B-1

Suspension Bail



33154-SCEP-04





61022-TH005 Tool Holder



33154-SCEP-03



Lock Nut Blue 61022-TH003

Tool Holder, diameter 58mm



D54SC#BV

Lock Nut Black



33116-SCEP-01 Protection Cover



00-4507

Torque Adjust Key RRI screwdriver



33154-SCEP-02 Lock Nut Red



Specifications

| Brand | RedRoosterIndustrial |
|------------------------------|----------------------|
| Bolt capacity (mm) | 5 |
| RPM | 300 - 800 |
| Torque (Nm) | 2 - 9 |
| Weight w/o battery (kg) | 1,0 |
| Hexagon | 1/4" |
| mm A | 203 |
| mm B | 238 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 0,4 |
| Vibration uncertainty (m/s²) | 1,5 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 65,6 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981400669 |
| | |

