

TORQUE WRENCH PRESET 40~200NM WPEMH14200BSN

FEATURES

- Accuracy: Torque: CW $\pm 4\%$ from 20% to 100% of capacity;
Angle: ($\pm 1\%$ of reading) + ($\pm 1^\circ$ @ angular speed of 10°/s~180°/s) + ($\pm 1^\circ$ of test fixture)
 - LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
 - Maintaining the Click audible alarm feature of the mechanical wrench.
 - 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
 - First peak value mode
 - Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
 - Peak value and judgment light status remain displayed after unloading.
 - WLAN Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.
- Version with barcode scanner.

Related accessories



QH911

End fitting 9x12, Ring End A/F 11mm



BQH915S

9x12 Ring Ratchet End 15 mm



DCQ6232

Setting tool (M) PCH models



OH910A15

End fitting 9x12, Open End 10 mm an



OH97

End fitting 9x12, Open End 7 mm



QOH913

9x12 Open Ring End 13mm



Specifications

Brand	NovaTork
Torque (Nm)	6 ~ 30
Weight (kg)	0,55
insert tool (mm)	9x12
mm D	24
L mm	248
EAN	8717981475827