

AUTO-SHUT-OFF SCREWDRIVER 0,4 ~ 2,2 NM RRI-SP10902

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- * New body-design (in composite)
- * Reversible
- * Revolving rear-exhaust, silenced
- * Pistol-version with air on top
- * ergonomic grip
- * easily adjustable

Related products



AC30A-F03E-B Modular FRL Unit



Spring Balancer Hosereel

Related accessories

HTB-0



61022-TH001 Tool Holder



00-4507

Torque Adjust Key RRI screwdriver




Air Tool Oil, 1 litre



Specifications

EAN

Brand	RedRoosterIndustrial
Bolt capacity (mm)	4
RPM	900
Torque (Nm)	0,4 - 2,2
Airconsumption (I/s)	8
Weight (kg)	0,77
Hexagon	1/4"
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	198
mm B	16
mm C	157
Hosediameter (mm)	6,5
Execution	Pistol
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	0,4
Vibration uncertainty (m/s²)	0,53
Sound standard	ISO 15744
Sound pressure (dB(A))	69,2
Sound uncertainty (dB(A))	2



8717981279180