

# AUTO-SHUT-OFF SCREWDRIVER 1,2~6,0NM ATEX RRI-SL21106-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIB T135°C.

#### Characteristics:

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

#### Related products



**HTB-0**  
Spring Balancer Hosereel

#### Related accessories



**00-4507**  
Torque Adjust Key RRI screwdriver



**ATLUB**  
Air Tool Oil, 1 litre



#### Specifications

|                                     |                        |
|-------------------------------------|------------------------|
| Brand                               | RedRoosterIndustrial   |
| Bolt capacity (mm)                  | 4                      |
| RPM                                 | 1100                   |
| Torque (Nm)                         | 1,2 - 6,0              |
| Airconsumption (l/s)                | 11                     |
| Weight (kg)                         | 0,87                   |
| Hexagon                             | 1/4"                   |
| Sound level (dB(A))                 | 73                     |
| Airconnection                       | PT 1/4"                |
| Airpress max. (MPa)                 | 0,63                   |
| mm A                                | 269                    |
| mm B                                | 39                     |
| mm C                                | 16                     |
| mm D                                | 15                     |
| Hosediameter (mm)                   | 6,5                    |
| Execution                           | Straight - lever start |
| Vibration level (m/s <sup>2</sup> ) | < 2,5                  |
| EAN                                 | 8717981460458          |

