

COMPOSITE IMPACT WRENCH 1/2 RR-18N T

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-18N T is especially developed for the tireshop applications. The Twin Hammer impact mechanism gives high energy levels per impact en thus suitable for heavy duty applications. The energy is directly transmmitted to the anvil for maximum power and low maintenance. The tool is limiting (*) the tightening torque for wheel nut applications, so overtightening is history! Full power available in loosening direction. Always use the torque wrench to check the torque!

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Exhaust silenced, through grip

Related products



D0605222601

Impact Socket Set 1/2"deep 26 parts



D0691121301

Impact Socket Set 1/2" & bits



D0611260501

Socketset 1/2" protected 5-Parts



AC30A-F03E-B

Modular FRL Unit





D069523108

Socketset 1/2" deep 10-Parts



D00012-0-286

Socketset 1/2" Lug Nut 7-Parts



D0652260701

Impact Socket Set 1/2" triple square



D061120310

3 Pc1/2"Dr.Wheel Nut Deep Socket S

Related accessories



EH-43-4033SUB

Exhaust Hose Assembly 1/4"



ATLUB

Air Tool Oil, 1 litre



Specifications

Brand	RedRooste
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
lmnost machanism	Turin Ham

Impact mechanism Twin-Hammer **RPM** 7000 Torque (Nm) 815 Force adjustment Airconsumption (I/s) 12.1 Weight (kg) 2,0 Tightening torque (Nm) Airconnection PT 1/4" 0,63 Airpress max. (MPa) 185 mm A 30 mm B

Hosediameter (mm) 10 Safety standard EN ISO 11148-6 EN ISO 28927-2 **Vibration standard** Vibration value (m/s²) 6,8 Vibration uncertainty (m/s²) 1,16 Sound standard ISO 15744 Sound pressure (dB(A)) 92,78 103.78 Sound power (dB(A))

8717981332502 **EAN**

Sound uncertainty (dB(A))

