

COMPOSITE IMPACT WRENCH 1/2

RR-18N T

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-18N T is especially developed for the tireshop applications. The Twin Hammer impact mechanism gives high energy levels per impact en thus suitable for heavy duty applications. The energy is directly transmitted to the anvil for maximum power and low maintenance. The tool is limiting (*) the tightening torque for wheel nut applications, so overtightening is history! Full power available in loosening direction. Always use the torque wrench to check the torque!



Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Exhaust silenced, through grip

Related products

-  **DO605222601**
Impact Socket Set 1/2" deep 26-parts
-  **DO691121301**
Impact Socket Set 1/2" & bits 13-parts
-  **DO611260501**
Impact Socket Set 1/2" protected 5-parts
-  **DO69523108**
Impact Socket Set 1/2" deep 10-parts
-  **DO0012-0-286**
Impact Socket Set 1/2" Lug Nut 7-parts
-  **DO652260701**
Impact Socket Set 1/2" triple square
-  **AC30A-F03E-D**
Frl Unit
-  **DO61120310**
Socket Set Wheel Nut Deep 1/2" 17/19/21

Related accessories

-  **EH-43-4033SUB**
Exhaust Hose Assembly 1/4"
-  **ATLUB**
Air Tool Oil, 1 litre



Specifications

Brand	RedRooster
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	7000
Torque (Nm)	815
Force adjustment	-
Airconsumption (l/s)	12,1
Weight (kg)	2,0
Tightening torque (Nm)	90
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	185
mm B	30
Hosediameter (mm)	10
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	6,8
Vibration uncertainty (m/s ²)	1,16
Sound standard	ISO 15744
Sound pressure (dB(A))	92,78
Sound power (dB(A))	103,78
Sound uncertainty (dB(A))	3
EAN	8717981332502

