

COMPOSITE IMPACT WRENCH 1/2 RR-18N T

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-18N T is especially developed for the tire shop applications. The Twin Hammer impact mechanism gives high energy levels per impact and thus suitable for heavy duty applications. The energy is directly transmitted to the anvil for maximum power and low maintenance. The tool is limiting (*) the tightening torque for wheel nut applications, so overtightening is history! Full power available in loosening direction. Always use the torque wrench to check the torque!



Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Exhaust silenced, through grip

Related products

-  D060522601
Impact Socket Set 1/2" deep 26 parts
-  D0691121301
Impact Socket Set 1/2" & bits
-  D0611260501
Socketset 1/2" protected 5-Parts
-  D00012-0-000S
Socketset 1/2" 10-Parts
-  AC30A-F03E-B
Modular FRL Unit
-  D069523108
Socketset 1/2" deep 10-Parts
-  D00012-0-286
Socketset 1/2" Lug Nut 7-Parts
-  D0652260701
Impact Socket Set 1/2" triple square
-  D061120310
3 Pc 1/2" Dr. Wheel Nut Deep Socket S

Related accessories

-  EH-43-4033SUB
Exhaust Hose Assembly 1/4"
-  ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	RedRooster
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	7000
Torque (Nm)	815
Force adjustment	-
Airconsumption (l/s)	12,1
Weight (kg)	2,0
Tightening torque (Nm)	90
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	185
mm B	30
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	6,8
Vibration uncertainty (m/s ²)	1,16
Sound standard	ISO 15744
Sound pressure (dB(A))	92,78
Sound power (dB(A))	103,78
Sound uncertainty (dB(A))	3
EAN	8717981332502

