

# COMPOSITE IMPACT WRENCH 1/2

## RR-18N T

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-18N T is especially developed for the tire shop applications. The Twin Hammer impact mechanism gives high energy levels per impact and thus suitable for heavy duty applications. The energy is directly transmitted to the anvil for maximum power and low maintenance. The tool is limiting (\*) the tightening torque for wheel nut applications, so overtightening is history! Full power available in loosening direction. Always use the torque wrench to check the torque!

### Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Exhaust silenced, through grip

### Related products



DO605222601

Impact Socket Set 1/2" deep 26-parts



DO691121301

Impact Socket Set 1/2" & bits 13-parts



DO611260501

Impact Socket Set 1/2" protected 5-parts



DO69523108

Impact Socket Set 1/2" deep 10-parts



DO0012-0-286

Impact Socket Set 1/2" Lug Nut 7-parts



DO652260701

Impact Socket Set 1/2" triple square



AC30A-F03E-D

Frl Unit



DO61120310

Socket Set Wheel Nut Deep 1/2" 17/19/21

### Related accessories



EH-43-4033SUB

Exhaust Hose Assembly 1/4"



ATLUB

Air Tool Oil, 1 litre



### Specifications

Brand	RedRooster
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	7000
Torque (Nm)	815
Force adjustment	-
Airconsumption (l/s)	12,1
Weight (kg)	2,0
Tightening torque (Nm)	90
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	185
mm B	30
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	6,8
Vibration uncertainty (m/s <sup>2</sup> )	1,16
Sound standard	ISO 15744
Sound pressure (dB(A))	92,78
Sound power (dB(A))	103,78
Sound uncertainty (dB(A))	3
EAN	8717981332502

