

# IMPULSE WRENCH 1/4 HEX ANGLE SHUT-O

## RRI-50RTA

The RED ROOSTER Impulse wrenches are handheld tools made for assembly with threaded fasteners. Impulse wrenches increase productivity. Typically meant for use in: Production of agricultural machinery, production of pumps, motors, bikes and any other serial production. The tool has a wide body air motor. Torque level adjustable in the impulse mechanism.

#### Characteristics:

- Lightweight
- Free of reaction forces
- Low noise and vibration levels
- Powerful and fast
- High repeatability of the torque level
- Angled model
- Auto shut off function

#### Related products



**AC30A-F03E-B**  
Modular FRL Unit

#### Related accessories

**01-0505Y0**  
standard accessories kit



**50R-RT008**  
Key Wrench for 50R, 60R, 70R



**ATLUB**  
Air Tool Oil, 1 litre



#### Specifications

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>Bolt capacity (mm)</b>	<b>6 - 8</b>
<b>RPM</b>	<b>4300</b>
<b>Torque (Nm)</b>	<b>9,5 - 16</b>
<b>Airconsumption (l/s)</b>	<b>4,8</b>
<b>Weight (kg)</b>	<b>1,20</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>253</b>
<b>mm B</b>	<b>45</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Square Drive / Hexagon</b>	<b>1/4"</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Vibration standard</b>	<b>EN ISO 28927-2</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>11,6</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>1,64</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>75,1</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981203925</b>

