

CHIPPING HAMMER 19X50 AA-1.3BR(H)19X50

Toku hammers have been used for many years in various industries, e.g Demolition, Foundries, Construction etc.

Characteristics:

- Toku only use the very best materials in the manufacture of their products giving the tools superior life.
- Version with a solid screw-retainer.
- The design of the solid retainer enables the use of pointed chisels as well as standard and wide.

Related products

- **CB5-G**
Wide Chisel bend TL=250 W=60
- **CB5**
Wide Chisel TL=300 B=60
- **MP5-350**
Moil Point TL= 400mm
- **MP5**
Moil Point TL= 325mm
- **NC5-450**
Flat Chisel TL=500 W=22
- **MP5-450**
Moil Point TL= 500mm
- **NC5-350**
Flat Chisel TL=400 W=22
- **NC5**
Flat Chisel TL=325 W=22



Specifications

Brand	Toku
Airconsumption (l/s)	7,5
Weight (kg)	4,5
Shank size (mm)	H^19 x 50
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	300
mm B	76
Stroke (mm)	58
Strokes per minute	2800
Energy (J/Stroke)	12,7
Hosediameter (mm)	10
Piston (mm)	24
Vibration standard	EN ISO 28927-10
Vibration value (m/s²)	23,5
Vibration uncertainty (m/s²)	2,60
Sound pressure (dB(A))	108
Sound power (dB(A))	119
Sound uncertainty (dB(A))	3
EAN	8717981182398

