









# CHIPPING HAMMER 19X50 AA-1.3BR(H)19X50

Toku hammers have been used for many years in various industries, e.g Demolition, Foundries, Construction etc.

## Characteristics:

- Toku only use the very best materials in the manufacture of their products giving the tools superior life.
- Version with a solid screw-retainer.
- The design of the solid retainer enables the use of pointed chisels as well as standard and wide.

## Related products

-  **CB5-G**  
Wide Chisel bend TL=250 W=60
-  **CB5**  
Wide Chisel TL=300 B=60
-  **MP5-350**  
Moil Point TL= 400mm
-  **MP5**  
Moil Point TL= 325mm
-  **NC5-450**  
Flat Chisel TL=500 W=22
-  **MP5-450**  
Moil Point TL= 500mm
-  **NC5-350**  
Flat Chisel TL=400 W=22
-  **NC5**  
Flat Chisel TL=325 W=22



## Specifications

<b>Brand</b>	<b>Toku</b>
<b>Airconsumption (l/s)</b>	<b>7,5</b>
<b>Weight (kg)</b>	<b>4,5</b>
<b>Shank size (mm)</b>	<b>H<sup>19</sup> x 50</b>
<b>Airconnection</b>	<b>PT 3/8"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>300</b>
<b>mm B</b>	<b>76</b>
<b>Stroke (mm)</b>	<b>58</b>
<b>Strokes per minute</b>	<b>2800</b>
<b>Energy (J/Stroke)</b>	<b>12,7</b>
<b>Hosediameter (mm)</b>	<b>10</b>
<b>Piston (mm)</b>	<b>24</b>
<b>Safety standard</b>	<b>EN ISO 11148-4</b>
<b>Vibration standard</b>	<b>EN ISO 28927-10</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>23,5</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>2,60</b>
<b>Sound pressure (dB(A))</b>	<b>108</b>
<b>Sound power (dB(A))</b>	<b>119</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981182398</b>

