RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

HIGH TORQUE GEAR WRENCH 1200 NM
RRI-BEC120S

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. Version with two-hand safety control. This gear wrench has an extremely high speed.

Characteristics:
- **Brushless motor**
- **36 Volt Lithium-Ion battery**
- **LED status indicates OK - NOK - REVERSE - BATTERY LOW**
- **Adjustable torque in 50 steps**
- **Display shows torque and setting**
- **automatic reaction arm release**
- **Tightening data retrievable via USB interface**

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.



Related accessories


31022-GW005
Sliding Reaction Plate RRI-BEC090/120


SW40-283-0102
Hanger


31084-360F
36V Charger


BW113
Back Up Wrench 12-Pt A/F 46 mm, max 4745 Nm


33257-RRI-BEC090
Standard Reaction Bar RRI-BEC090/120


31022-GW001
Reaction Bar RRI-BEC025-250


31022-GW003
Single-Sided Reaction Plate RRI-BEC090/120


31022-GW010
Reaction Bar RRI-BEC025-250


31022-GW002
Reaction Bar Adapter RRI-BEC090/120


Koffer RRI-BEC120
Case RRI-BEC120


31022-GW007
Secondary Handle RRI-BEC/120/150/250


DOESR-2
Ret Ring 3/4"


31022-GW009
Reaction Bar RRI-BEC025-250


31022-GW004
Double-Sided Reaction Plate RRI-BEC090/120


31022-GW018
Reaction Welding Ring RRI-BEC090/120

Specifications

Brand	**RedRoosterIndustrial**
Square Drive	**3/4"**
Bolt capacity (mm)	**18 ~ 30**
RPM	**88 / 15**
Torque (Nm)	**240 ~ 1200**
Weight w/o battery (kg)	**5,0**
mm A	**145**
mm B	**75**
mm C	**322**
mm D	**228**
mm E	**269**
mm F	**Ø 82**
mm L	**54**
Battery voltage (Volt)	**36**
Battery type Li-ion….(Ah)	**5,0**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**1**
Vibration uncertainty (m/s²)	**1,5**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**82**
Sound uncertainty (dB(A))	**3**
EAN	**8717981454464**

