

CHIPPING HAMMER BRH-6



















This Yokota chipping hammer is supplied with open and closed spring retainer for the chisel. High blow-energy. For practical use in construction, building and automotive aftermarket. Industrial quality.

Characteristics:

- * Ergonomic design, well balanced.
- * Compact and lightweight.
- * Suits both left- and right-handers.

Delivery includes rivet snap D6mm 6101-0821-00-04

Related products

-  **BE101006**
Bushingsplittertool
-  **BE101022**
Moilpointchisel
-  **BE101017**
Spotweld Breaker
-  **BE101003**
Sheetmetaltrimmer
-  **BE101025**
Rivet Cutter
-  **BE101005**
Mufflercutter
-  **BE101008**
Bushing Driver
-  **BE101027**
Centerpunchchisel
-  **BE101018**
Scraper
-  **BE101021**
Wide Cuttingchisel
-  **BE101010**
Flat Chisel
-  **BE101028**
Pin Punch
-  **BE101016**
Straight Punch
-  **BE101019**
Tailpipecutter
-  **BE101007**
Spotweldbreaker Bend
-  **BE101024**
Bent Flatchisel
-  **BE101002**
Flat Chisel
-  **BE101011**



Specifications

Brand	Yokota
Airconsumption (l/s)	6,6
Weight (kg)	1,4
Sound level (dB(A))	95
Shank size (mm)	R ^{10,2} x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	200
mm B	149
Stroke (mm)	60
Strokes per minute	3500
Energy (J/Stroke)	9,0
Hosediameter (mm)	10
Vibration level (m/s ²)	17
Piston (mm)	20
Safety standard	EN ISO 11148-4
EAN	8717981040858

