

# CHIPPING HAMMER BRH-6

















This Yokota chipping hammer is supplied with open and closed spring retainer for the chisel. High blow-energy. For practical use in construction, building and automotive aftermarket. Industrial quality.

Characteristics:

- Ergonomic design, well balanced.
- Compact and lightweight.
- Suits both left- and right-handers.

Delivery includes rivet snap D6mm 6101-0821-00-04

## Related products

-  **BE101006**  
Bushingsplittertool
-  **BE101022**  
Moilpointchisel
-  **BE101017**  
Spotweld Breaker
-  **BE101003**  
Sheetmetaltrimmer
-  **BE101025**  
Rivet Cutter
-  **BE101008**  
Bushing Driver
-  **BE101027**  
Centerpunchchisel
-  **BE101018**  
Scraper
-  **BE101021**  
Wide Cuttingchisel
-  **BE101010**  
Flat Chisel
-  **BE101028**  
Pin Punch
-  **BE101016**  
Straight Punch
-  **BE101019**  
Tailpipecutter
-  **BE101007**  
Spotweldbreaker Bend
-  **BE101002**  
Flat Chisel
-  **BE101011**  
Double Edged Cutter



## Specifications

Brand	Yokota
Airconsumption (l/s)	6,6
Weight (kg)	1,4
Sound level (dB(A))	95
Shank size (mm)	R <sup>10,2</sup> x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	200
mm B	149
Stroke (mm)	60
Strokes per minute	3500
Energy (J/Stroke)	9,0
Hosediameter (mm)	10
Vibration level (m/s <sup>2</sup> )	17
Piston (mm)	20
EAN	8717981040858

