

IMPACT WRENCH 1" MI-42ESR

This industrial impact wrench by Toku has proven capabilities. The MI-42ESR is developed for tightening and untightening applications. The Twin Hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is especially suitable for use in heavy jobs in the tire industry.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable, 4 positions

Related products



D00100-1-007

Impact Socket Set Long 1" 7-parts



AC40A-F04-D

Modular FRL unit

Related accessories



ATLUB

Air Tool Oil, 1 litre



DOESR-3

Ret Ring



Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	42
Impact mechanism	Twin-Hammer
RPM	3900
Torque (Nm)	2850
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	23
Weight (kg)	9,4
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	370
mm B	60
Hosediameter (mm)	13
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	15,2
Vibration uncertainty (m/s²)	2,00
Sound standard	ISO 15744
Sound pressure (dB(A))	101
Sound power (dB(A))	112
Sound uncertainty (dB(A))	3
EAN	8717981011544

