

AUTO-SHUT-OFF SCREWDRIVER 0,7~2,3NM

RRI-SP23102

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- New body-design
- Reversible
- Revolving rear-exhaust, silenced
- ergonomic grip
- easily adjustable

Related products



TW-0
Spring Balancer 0,5-1,5kg

Related accessories



61022-TH001
Tool Holder



00-4507
Torque Adjust Key RRI screwdriver



ATLUB
Air Tool Oil, 1 litre



Specifications

| | |
|---|----------------------|
| Brand | RedRoosterIndustrial |
| Bolt capacity (mm) | 3 |
| RPM | 3100 |
| Torque (Nm) | 0,7 ~ 2,3 |
| Airconsumption (l/s) | 11 |
| Weight (kg) | 1,02 |
| Hexagon | 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 208 |
| mm B | 16 |
| mm C | 166 |
| mm D | 37,2 |
| Hosediameter (mm) | 6,5 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | <2,5 |
| Vibration uncertainty (m/s ²) | 0,1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 79 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981428144 |

