

IMPACT WRENCH 1" MI-3800ESR

This industrial impact wrench by Toku has proven capabilities. The MI-3800ESR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable, 4 positions

Related products



DO0100-1-007
 Impact Socket Set Long 1" 7-parts

Related accessories



ATLUB
 Air Tool Oil, 1 litre



DOESR-3
 Ret Ring



Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	36
Impact mechanism	Gesloten Hamer
RPM	4500
Torque (Nm)	2100
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	15
Weight (kg)	9,3
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	355
mm B	55
Hosediameter (mm)	13
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	10,4
Vibration uncertainty (m/s²)	1,52
Sound pressure (dB(A))	96
Sound power (dB(A))	107
Sound uncertainty (dB(A))	ISO 15744
EAN	8717981000203

