YOKOTA

CONTROLLED PRECISION IN TIGHTENING

IMPULSE WRENCH 3/8" 33-50NM YLA80E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.



Related accessories

0191-0029-01-00
Rubber protection cover YLA80



61022-TH002
Tool Holder, diameter 47mm



ATLUB
Air Tool Oil, 1 litre

Specifications

Brand	Yokota
Bolt capacity (mm)	8
RPM	7000
Torque (Nm)	33 - 50
Weight (kg)	0,9
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	5,8
mm A	139
mm B	22
Hosediameter (mm)	6,5
Square Drive / Hexagon	3/8"
Air consumption no load (l/s)	9
Vibration standard	EN ISO 28927-2
Vibration value (m/s^2)	< 2,5
Vibration uncertainty (m/s^2)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	75
Sound uncertainty (dB(A))	3
EAN	8717981038312

