

IMPULSE WRENCH 3/8"

YLA80E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

Related products



AC30A-F03E-B
 Modular FRL Unit

Related accessories

0191-0029-01-00

Rubber protection cover YLA80



61022-TH002
 Tool Holder, diameter 47mm



ATLUB
 Air Tool Oil, 1 litre



Specifications

| | |
|---|----------------|
| Brand | Yokota |
| Bolt capacity (mm) | 8 |
| RPM | 7000 |
| Torque (Nm) | 33 - 50 |
| Weight (kg) | 0,9 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| Airconsumption fullload (l/s) | 5,8 |
| mm A | 139 |
| mm B | 22 |
| Hosediameter (mm) | 6,5 |
| Square Drive / Hexagon | 3/8" |
| Safety standard | EN ISO 11148-6 |
| Air consumption no load (l/s) | 9 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | < 2,5 |
| Vibration uncertainty (m/s ²) | 1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 75 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981038312 |

