

ANGLE GRINDER 230MMX22MM TAG-900QJL

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * For cutting and grinding purposes
- * Exhaust silenced
- * Low vibration level

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



2400-046-11
Dead Handle Vibration Red.



2700-041-00
Set Screw



2700-040-00
Wheel Ring



9610-1010-00-00
Hex Wrench H10



ATLUB
Air Tool Oil, 1 litre



8081-0022-00-00
Spanner TAG-700QJL / TAG-900QJL



Specifications

Brand	Toku
RPM	6500
Airconsumption (l/s)	16,6
Weight (kg)	3,1
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	307
mm B	103
mm C	36
mm D	62
Hosediameter (mm)	13
Spindle	Toku System
Power (kW)	1,10
Wheel size (mm)	230 x (1,9 - 8) x 22,2
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-1
Vibration value (m/s²)	7,9
Vibration uncertainty (m/s²)	2,61
Sound standard	ISO 15744
Sound pressure (dB(A))	87
Sound power (dB(A))	98
Sound uncertainty (dB(A))	3
EAN	8717981047635

