

# CHIPPING HAMMER H19X50 THA-4BRH19X50

Toku hammers have been used for many years in various industries, e.g Demolition, Foundries, Construction etc.









## Characteristics:

\* Toku only use the very best materials in the manufacture of their products giving the tools superior life.

\* Due to popular demand we have included a version of this tool to our range with a solid retainer.

\* The design of the solid retainer enables the use of pointed chisels as well as standard and wide.

## Related products

-  **CB5-G**  
Wide Chisel bend TL=250 W=60
-  **CB5**  
Wide Chisel TL=300 B=60
-  **MP5-350**  
Moil Point TL= 400mm
-  **MP5**  
Moil Point TL= 325mm
-  **NC5-450**  
Flat Chisel TL=500 W=22
-  **MP5-450**  
Moil Point TL= 500mm
-  **NC5-350**  
Flat Chisel TL=400 W=22
-  **NC5**  
Flat Chisel TL=325 W=22



## Specifications

Brand	Toku
Airconsumption (l/s)	15,8
Weight (kg)	7,8
Shank size (mm)	H <sup>19</sup> x 50
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	430
mm B	87
Stroke (mm)	102
Strokes per minute	1800
Energy (J/Stroke)	31,8
Hosediameter (mm)	13
Piston (mm)	28,5
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-10
Vibration value (m/s <sup>2</sup> )	28,0
Vibration uncertainty (m/s <sup>2</sup> )	3,00
Sound standard	ISO 15744
Sound pressure (dB(A))	110
Sound power (dB(A))	121
Sound uncertainty (dB(A))	3
EAN	8717981214204

