

# PAVEMENT BREAKER (25X108MM)









## RRI-4720K

This RED ROOSTER INDUSTRIAL pavement breaker has a chisel retainer with latch. Suitable for endured usage. High energy level each blow. For applications in construction and renovations.

**Characteristics:**

- Ergonomic design, well balanced
- Compact quality tool
- Integrated noise muffler
- with air cushioned piston

**Related products**

-  **NC3**  
Flat Chisel TL=490 W=25
-  **MP3**  
Moil Point TL=500
-  **AC3**  
Asphalt Cutter TL=400 W=125
-  **MP3-450**  
Moil Point TL= 600
-  **NC3-450**  
Flat Chisel TL=600 W=25
-  **NC3-1500**  
Flat Chisel TL=1600 W=25
-  **DC3**  
Digger steel TL=500 W=75
-  **CB3**  
Wide Chisel TL=465 W=75



**Specifications**

<b>Brand</b>	RedRoosterIndustrial
<b>Airconsumption (l/s)</b>	23
<b>Weight (kg)</b>	22
<b>Shank size (mm)</b>	H <sup>25</sup> x 108
<b>Airconnection</b>	PT 3/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	631
<b>mm B</b>	453
<b>Stroke (mm)</b>	136
<b>Strokes per minute</b>	1200
<b>Energy (J/Stroke)</b>	60
<b>Hosediameter (mm)</b>	19
<b>Piston (mm)</b>	40
<b>Vibration standard</b>	EN ISO 28927-10
<b>Vibration value (m/s<sup>2</sup>)</b>	9,8
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,5
<b>Sound standard</b>	2000/14/EC
<b>Sound pressure (dB(A))</b>	86
<b>Sound power (dB(A))</b>	105
<b>Sound uncertainty (dB(A))</b>	1,8
<b>EAN</b>	8717981427680

