

AIR CHAIN HOIST 25000 KG TMH-25TP2E

The RED ROOSTER TMH series air chain hoists has the highest lifting speed on the hoist market. With M3 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for installation.

Standard features:

- Precise variable speed control (pendant control)
- Optimum control of the load, very precise positioning • Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

Related products



42-02-28-VRD

Pendant Valve Assy TCR/TMH



SO-112392-AC825-14

Filter/Regulator/Lubricator 1-1/2"



23,5X66

Chain EN 818-7



Specifications

Brand	RedRooster
Number of chain falls	2
Lowering speed full load (m/min)	3,0
Weight incl. 3m lift (kg)	581
Lifting speed full load (m/min)	1,4
Lifting speed 0-load (m/min)	2,7
Chain weight (kg/m)	12,1
Chain (mm)	23,5 x 66
Chainbag/Chainbucket	+
Loadlimiter	*
Airconnection	1,5" BSPT
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	108
mm A	1290
mm B	566
mm C	223
mm D	343
mm E	330
mm F	82
mm G	285
mm H	708
mm I	352
mm J	356
mm K	90
mm L	100
mm M	71
mm N	732
mm O	558
mm P	71
mm Q	100
mm R	90
Hosediameter (mm)	38
SMC Airtreatment unit	SO-112392-AC825-14