









PAVEMENT BREAKER (32X160MM) RRI-4725K VL

This RED ROOSTER INDUSTRIAL pavement breaker has a chisel retainer with latch. Suitable for endured usage. High energy level each blow. For applications in construction and renovations.

Characteristics:

- Ergonomic design, well balanced
- Compact quality tool
- Integrated noise muffler
- Vibration reduced handle bars

Related products

-  **MP1A**
Moil Point TL= 550
-  **AC1**
Asphalt Cutter TL=440 W=115
-  **CB5019**
Asphalt Cutter TL=445 W=125
-  **MP1**
Moil Point TL= 610
-  **CB1A**
Wide Chisel TL=550 W=76
-  **NC1A**
Flat Chisel TL=550 W=32
-  **NC1**
Flat Chisel TL=610 W=32
-  **DC1**
Digger steel TL=530 W=75



Specifications

Brand	RedRoosterIndustrial
Airconsumption (l/s)	28
Weight (kg)	25
Shank size (mm)	H^32 x 160
Airconnection	PT 3/4"
Airpress max. (MPa)	0,63
mm A	694
mm B	441
Stroke (mm)	138
Strokes per minute	1440
Energy (J/Stroke)	65
Hosediameter (mm)	19
Piston (mm)	42
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-10
Vibration value (m/s²)	3,4
Vibration uncertainty (m/s²)	1,5
Sound standard	2000/14/EC
Sound pressure (dB(A))	87
Sound power (dB(A))	102
Sound uncertainty (dB(A))	1,9
EAN	8717981427703

