

BELT SANDER 12X610/6X610 RRG-3612

This robust belt sander by RED ROOSTER is designed for deburring in narrow and confined spaces. For use in nearly all materials, steel, aluminum, plastics and wood. For fine work, a grinding arm for 6mm belts is also included in the package.

Characteristics:

- Ergonomic design, well balanced
- Exhaust silenced
- Easy change of sanding belts
- Extended service life of sanding belt
- Motor case can revolve 360 degrees for better ergonomics

Related accessories

-  SSB60660-610
Sanding Belt 6X610/60
-  SSB612120
Sanding Belt 12X610/120
-  SSB612100
Sanding Belt 12X610/100
-  SSB61260
Sanding Belt 12X610/60
-  SSB612150
Sanding Belt 12X610/150
-  SSB606150-610
Sanding Belt 6X610/150
-  SSB606120-610
Sanding Belt 6X610/120
-  SSB61280
Sanding Belt 12X610/80
-  SSB606100-610
Sanding Belt 6X610/100
-  SSB60680-610
Sanding Belt 6X610/80



Specifications

| | |
|-------------------------------------------|----------------|
| Brand | RedRooster |
| RPM | 20000 |
| Airconsumption (l/s) | 13,7 |
| Weight (kg) | 1,37 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 65 |
| mm B | 386 |
| Sandingbelt | 12 x 610 |
| Hosediameter (mm) | 10 |
| Power (kW) | 0,5 |
| Safety standard | EN ISO 11148-8 |
| Vibration standard | EN ISO 28927-1 |
| Vibration value (m/s ²) | 2,36 |
| Vibration uncertainty (m/s ²) | 0,52 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 86 |
| Sound power (dB(A)) | 97 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981397259 |

