YOKOTA

CONTROLLED PRECISION IN TIGHTENING

IMPULSE WRENCH 3/8 13-22NM YLA60E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

Related accessories

0189-0029-00-00

Rubber protection cover YLA60 /70



61022-TH002

Tool Holder, diameter 47mm



Specifications

Brand	**Yokota**
Bolt capacity (mm)	**6**
RPM	**4000**
Torque (Nm)	**13 - 22**
Weight (kg)	**0,78**
Airconnection	**PT 1/4"**
Airpress max. (MPa)	**0,63**
Airconsumption fullload (l/s)	**5,0**
mm A	**130**
mm B	**22**
Hosediameter (mm)	**6,5**
Square Drive / Hexagon	**3/8"**
Air consumption no load (l/s)	**5,5**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**< 2,5**
Vibration uncertainty (m/s²)	**1**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**71**
Sound uncertainty (dB(A))	**3**
EAN	**8717981265169**

