

# IMPULSE WRENCH 3/8

## YLA60E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

### Related products



**AC30A-F03E-B**  
 Modular FRL Unit

### Related accessories

0189-0029-00-00

Rubber protection cover YLA60 /70



**61022-TH002**  
 Tool Holder, diameter 47mm



### Specifications

Brand	Yokota
Bolt capacity (mm)	6
RPM	4000
Torque (Nm)	13 - 22
Weight (kg)	0,78
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	5,0
mm A	130
mm B	22
Hosediameter (mm)	6,5
Square Drive / Hexagon	3/8"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	5,5
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	< 2,5
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	71
Sound uncertainty (dB(A))	3
EAN	8717981265169

