

SYSTEM WRENCH 3/4"

YEX-3000

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Product liability is essential to carmakers. All tightened joints have to be correct. For this reason all bolted joints must be counted, documented and, of course, tightened with the right clamping force. In order to do this, you need an impulse wrench (with a built-in transducer) connected to a controller. If the controller establishes that the tightened joints do not meet the specifications, it can give a line-stop signal and the joints have to be checked manually.


Characteristics:

- * Very low weight / torque ratio
- * High speed fastening
- * No Kickback
- * Acoustic status-signals on back-cover

Related accessories



YETC-2SVD 1/2
Double Solenoidvalve 24V



Specifications

Brand	Yokota
Bolt capacity (mm)	16
RPM	4000
Torque (Nm)	186 - 284
Airconsumption (l/s)	10,0
Weight (kg)	6,4
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	309
mm B	40
Hosediameter (mm)	12,7
Square Drive / Hexagon	3/4"
Air consumption no load (l/s)	20,5
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	3,1
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	80
Sound power (dB(A))	91
Sound uncertainty (dB(A))	3
EAN	8717981179992

