

ANGLE GRINDER 115MMX22MM TAG-45MLH

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * For cutting and grinding purposes
- * Exhaust silenced
- * Low vibration level
- * M14 Spindle

Related accessories



2400-046-11
 Dead Handle Vibration Red.

13-40-04-014

Combi Spanner 14x19

13-08-02-147

Socket Bar



QN-M14
 Quick Nut M14X2.0P



ATLUB
 Air Tool Oil, 1 litre

9310-3008-00-00

Rubber pad D100 with M14 flange

42-05-80-H00

Wheel Ring



Specifications

Brand	Toku
RPM	13000
Airconsumption (l/s)	10,8
Weight (kg)	1,6
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	267
mm B	85
mm C	33
mm D	50
Hosediameter (mm)	10
Spindle	M14 x 2
Power (kW)	0,67
Wheel size (mm)	115 x (0,8 - 7) x 22,2
Vibration standard	EN ISO 28927-1
Vibration value (m/s²)	11,7
Vibration uncertainty (m/s²)	3,85
Sound pressure (dB(A))	93
Sound power (dB(A))	104
Sound uncertainty (dB(A))	3
EAN	8717981036295

