YOKOTA
CONTROLLED PRECISION IN TIGHTENING

DRILL 8-10 MM 1900 RPM
YRD-8NBK

This Yokota drill is suitable for industrial applications. The two-step trigger allows easy setting of the drill tip at first stage, and afterward high rpm for maximum drilling-speed.
Characteristics:
*** Compact and lightweight**
*** Low vibrationlevel**
*** Exhaust through grip, with silencer**
*** Ergonomic design**
*** Includes 10 mm key-less drill chuck**

Related accessories



BHS-10MM
Drill Chuck (Quick Change) 3/8X24Nf



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	**Yokota**
RPM	**1900**
Airconsumption (l/s)	**10,0**
Weight (kg)	**1,30**
Drill chuck	**3/8" x 24UNF**
Capacity steel (mm)	**8 - 10**
Direction	**R**
Airconnection	**PT 1/4"**
Airpress max. (MPa)	**0,63**
mm A	**176**
mm B	**150**
mm C	**25**
Hosediameter (mm)	**10**
Power (kW)	**0,38**
Vibration standard	**EN ISO 28927-5**
Vibration value (m/s²)	**< 2,5**
Vibration uncertainty (m/s²)	**1**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**80**
Sound power (dB(A))	**91**
Sound uncertainty (dB(A))	**3**
EAN	**8717981000685**

