

# DRILL 8-10 MM 1900 RPM YRD-8NBK

This Yokota drill is suitable for industrial applications. The two-step trigger allows easy setting of the drill tip at first stage, and afterward high rpm for maximum drilling-speed.

**Characteristics:**

- \* Compact and lightweight
- \* Low vibration level
- \* Exhaust through grip, with silencer
- \* Ergonomic design
- \* Includes 10 mm key-less drill chuck

**Related products**



**AC30A-F03E-B**  
Modular FRL Unit

**Related accessories**

**BHS-10MM**

Drill Chuck (Quick Change) 3/8X24Nf



**ATLUB**  
Air Tool Oil, 1 litre



**Specifications**

Brand	Yokota
RPM	1900
Airconsumption (l/s)	10,0
Weight (kg)	1,30
Drill chuck	3/8" x 24UNF
Capacity steel (mm)	8 - 10
Direction	R
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	176
mm B	150
mm C	25
Hosediameter (mm)	10
Power (kW)	0,38
Safety standard	EN ISO 11148-3
Vibration standard	EN ISO 28927-5
Vibration value (m/s <sup>2</sup> )	< 2,5
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	80
Sound power (dB(A))	91
Sound uncertainty (dB(A))	3
EAN	8717981000685

