


20V-3/8" SQ, TRANSDUCER SCREWDRIVER RRI-BCP16S3

RED ROOSTER Cordless transducerized screwdriver. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.

Characteristics:

- Brushless motor
- 20 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Tightening mode setting – Torque or Angle
- Programmable torque
- Programmable angle limits
- Programmable speed
- Group check / counting
- 8 programs including sequence
- Compact and light weight
- The flat battery pack offers stability
- Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

Related products

-  **BB200D-325**
20V 2.5Ah Battery, Li-ion
- BB200D-350**
20V 5.0Ah Battery, Li-ion
- B84192B**
18-20V Charger

Related accessories

-  **D39SC180B-1**
Suspension Bail
-  **33116-B200D-01**
Protection Cover
- 766-027-612**
Side handle for BCP
-  **61022-TH005**
Tool Holder
-  **32088-NPA-01**
Cable
-  **33116-B200D-02**
Protection Cover
-  **61022-TH003**
Tool Holder, diameter 58mm
- 33116-NPA-01**
Protection Cover RRI-BCP



Specifications

| | |
|-----------------------------|----------------------|
| Brand | RedRoosterIndustrial |
| Square Drive | 3/8" |
| Bolt capacity (mm) | 6 |
| RPM | 100 - 500 |
| Torque (Nm) | 5 - 16 |
| Weight w/o battery (kg) | 1,01 |
| mm A | 202,5 |
| mm B | 240,5 |
| Battery voltage (Volt) | 20 |
| Battery type Li-ion....(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | < 75 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981418671 |

